

Premier™ Combination Series

Specification-grade, LED, thermoplastic, snap-together combination unit



—
01
Remote capable
exit sign



nexus



Nexus®Pro



Construction

- White or black UV stabilized thermoplastic enclosure
- Clear polycarbonate lens covers
- Choice of MR16 LED lamp wattages
- 6 inch EXIT lettering legend, available in red or green
- Field-selectable chevrons

Mounting

- Surface mount
- Canopy included for ceiling mount applications
- Universal J-box mounting

Choice of battery

- 6V or 12V lead-calcium battery
- 6V or 12V nickel-metal hydride battery

Special wording panels

- Available, contact your sales representative with your design requirements

Photometric performance

Lamp	Spacing center-to-center (feet)	
	7' mounting height	15' mounting height
LA	39'	34'
LB	74'	57'
LG	49'	39'
LI	68'	54'
LJ	89'	80'


Housing color



White



Black



Electronics

- Optional Advanced Diagnostics
- Optional Nexus®Pro IoT monitoring system
- Optional Nexus® wired and wireless monitoring system
- 120/277 60Hz

Approvals

- UL 924 standards listed
- Nickel-metal hydride battery combination units UL listed for damp location (50°F to 104°F, 10°C to 40°C)
- Meets NFPA101 (Life Safety Code), NFPA 70 NEC, OSHA illumination standards

Warranty


- Unit has a five-year warranty
- Detailed warranty terms located on page 202 or online at:
www.emergi-lite.com/usa/files/EL_Warranty.pdf

Double face configurations

Convert single face to double face in the field	
Red/white	005715-E
Red/black	005716-E
Green/white	005717-E
Green/black	005718-E

Dimensions

Dimensions are approximate and subject to change.



Power consumption and unit rating

Exit sign module	Battery type	AC specs	1-1/2 hrs	2 hrs	3 hrs	4 hrs
612M	Lead-calcium	120/277VAC, 60HZ	0.11 / 0.05 A	12	8	–
624M	Lead-calcium		0.11 / 0.05 A	24	16	12
1224M	Lead-calcium		0.22 / 0.08 A	24	16	12
612H	Nickel-metal hydride		0.11 / 0.05 A	12	9	–
1224H	Nickel-metal hydride		0.22 / 0.08 A	24	18	12
1240H	Nickel-metal hydride		0.22 / 0.08 A	40	30	20
1250H	Nickel-metal hydride		0.22 / 0.08 A	50	36	24

Accessories (order as a separate item)

Description	Suffix
Wire guard (wall mount)	WG2-E
Pendant white	PRE-P-WH ¹
Pendant black	PRE-P-BK ¹

¹Specify pendant length in inches

How to order

Housing color	Series	Voltage/capacity/battery	Faces	Legend color
W= White B= Black	PR= Series	Lead-calcium 612M= 6V-12W, lead-calcium 624M= 6V-24W, lead-calcium 1224M= 12V-24W, lead-calcium Nickel-metal hydride 612H= 6V-12W, NiMH, rated damp location 1224H= 12V-24W, NiMH, rated damp location 1240H= 12V-40W, NiMH, rated damp location 1250H= 12V-50W, NiMH, rated damp location	1= Single face (ceiling or wall mount) 1N= Single face no canopy (wall mount) 2= Double face (ceiling mount) 4= Universal (2 faces, back plate and canopy)	G= Green legend R= Red legend

# of heads	Lamp type/wattage	Options
Blank= No heads 2= Two heads	LA= 6V-4W, MR16 LED LB= 6V-5W, MR16 LED LG= 12V-4W, MR16 LED LI= 12V-5W, MR16 LED LJ= 12V-6W, MR16 LED	Blank= No option -AD= Advanced Diagnostics (audible) ¹ -ADNA= Advanced Diagnostics (non-audible) ¹ -NEX= Nexus® wired ¹ -NEXP= Nexus®Pro IoT ¹ -NEXRF= Nexus® wireless ¹ -BA= Brushed aluminum exit stencil -D3= Time delay (15 minutes) -FA= Fire alarm activated flasher -FBF= Flasher buzzer + fire alarm activated flasher -FL= Flasher -FZ= Flasher buzzer -VR= Tamper-proof screws ² -VR1= Polycarbonate shield with tamper-proof screws ¹

Example: WPR612M1R2LA

¹Not available with 1250H, must connect minimum 20% load capacity

²Not available with universal faces